

ZPMV2.E48920

Wiring, Printed - Component

SPRIG CIRCUITS INC
 765 B EUBANKS DR
 VACAVILLE, CA 95688 USA

E48920

	Cond Width		Cond	SS/ DS	Max Area Diam mm(in)	Solder		Max Oper Temp C	Flame Class	Meets UL796 UL796 DSR	C T I
	Min	Edge				Thk	Limits				
Type	mm(in)	mm(in)	mic(mil)		mm(in)	C	sec	C	Class	DSR	I
Mass laminated printed wiring boards.											
S-2V-0	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-0	All	4
Single layer printed wiring boards.											
N-2V-0 (e)	0.13 (0.005)	0.13 (0.005)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-0	All	4
N-2V-1	0.2 (0.008)	0.61 (0.024)	17 (0.67)	DS	25.4 (1.0)	260	10	105	V-1	All	4
N-3V-0	0.15 (0.006)	0.46 (0.018)	17 (0.67)	DS	76.2 (3.0)	274	20	130	V-0	All	-
N-4V-0	0.15 (0.006)	0.46 (0.018)	34 (1.34)	DS	12.7 (0.5)	274	20	130	V-0	All	-

(e) - Maximum external copper thickness is 5.35 mils.

Marking: Company name or tradename "SPRIG" and type designation. May be followed by a suffix to denote factory identification.

[Last Updated](#) on 2006-01-19