

ZPMV2.E52909 - WIRING, PRINTED - COMPONENT

Wiring, Printed - Component

See General Information for Wiring, Printed - Component



WESTAK INC1116 Elko Dr
Sunnyvale, CA 94089 USA

E52909

Type	Cond Width		Cond Thk mic(mil)	SS/ DS/ DSO	Max	Max		Meets C			
	Min	Min			Area	Solder	Oper	Flame	UL796	T	
	Min	Edge			Diam	Limits	Temp	Class	UL796	DSR	I
	mm(in)	mm(in)			mm(in)	C sec	C		Class	DSR	I
Mass laminated (multilayered) printed wiring boards.											
1G	0.05 (0.002)	0.05 (0.002)	15 (0.59)	DS	101.6 (4.0)	288	20	130	V-0	All	3
Multilayer printed wiring boards.											
8A*	0.13 (0.005)	0.3 (0.012)	16.5 (0.65) Int:102	DS	76.2 (3.0)	260	20	105	V-0	All	-
8B*	0.13 (0.005)	0.3 (0.012)	16.5 (0.65) Int:16.5	DS	76.2 (3.0)	260	20	120	V-0	All	-
8C	0.05 (0.002)	0.15 (0.006)	8.1 (0.32) Int:102	DS	76.2 (3.0)	274	20	130	V-0	All	3
8D	0.05 (0.002)	0.15 (0.006)	8.1 (0.32) Int:102	DS	76.2 (3.0)	274	20	130	V-0	All	3
8E	0.07 (0.003)	0.09 (0.004)	17 (0.67) Int:102	DS	101.6 (4.0)	288	20	130	V-0	All	3
8F	0.05 (0.002)	0.05 (0.002)	8.5 (0.33) Int:102	DS	101.6 (4.0)	274	20	130	V-0	All	*
8G	0.05 (0.002)	0.05 (0.002)	8.5 (0.33) Int:102	DS	50.8 (2.0)	274	20	130	V-0	All	*
8H	0.05 (0.002)	0.05 (0.002)	17 (0.67) Int:102	DS	101.6 (4.0)	288	20	140	V-0	All	4
8I	0.05 (0.002)	0.05 (0.002)	12 (0.47) Int:102	DS	76.2 (3.0)	274	20	130	V-0	All	3
8J	0.1 (0.004)	0.06 (0.002)	17 (0.67) Int:102	DS	76.2 (3.0)	260	20	130	V-0	All	-

8M	0.05 (0.002)	0.05 (0.002)	17 (0.67) Int:70	DS	101.6 (4.0)	288	20	130	V-0	All	3
8N	0.05 (0.002)	0.15 (0.006)	8.5 (0.33) Int:102	DS	76.2 (3.0)	274	20	130	V-0	All	*
Multilayer Printed Wiring Boards.											
8O	0.05 (0.002)	0.05 (0.002)	9 (0.35) Int:136	DS	76.2 (3.0)	274	20	130	V-0	All	3
Multilayer printed wiring boards, flammability only Recognition.											
8R	-	-	-	DS	-	260	20	-	V-0	-	-
Single layer printed wiring boards.											
1C	0.08 (0.003)	0.15 (0.006)	8.1 (0.32)	DS	76.2 (3.0)	274	20	130	V-0	All	3
1D	0.05 (0.002)	0.15 (0.006)	8.1 (0.32)	DS	76.2 (3.0)	274	20	130	V-0	All	3
1E	0.05 (0.002)	0.15 (0.006)	17.3 (0.68)	DS	76.2 (3.0)	274	20	130	V-0	All	-
1F	0.05 (0.002)	0.05 (0.002)	8.5 (0.33)	DS	101.6 (4.0)	274	20	130	V-0	All	*
1H	0.07 (0.003)	0.09 (0.004)	17 (0.67)	DS	101.6 (4.0)	288	20	130	V-0	All	3
1I	0.05 (0.002)	0.05 (0.002)	12 (0.47)	DS	76.2 (3.0)	274	20	130	V-0	All	3
1N	0.05 (0.002)	0.15 (0.006)	8.5 (0.33)	DS	76.2 (3.0)	274	20	130	V-0	All	*
1P	0.17 (0.007)	0.15 (0.006)	34 (1.34)	DS	101.6 (4.0)	274	20	130	V-0	All	4

* - CTI marking is optional and may be marked on the printed wiring board.

Marking: Company name or trademark  ,  or file number and type designation. May be followed by a suffix to denote factory identification or burning test classification.

Last Updated on 2018-01-13

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".

UL and the UL logo are trademarks of UL LLC ©2018 All Rights Reserved.
[About](#) [Privacy Policy](#) [Terms & Conditions](#) [Access Your Data](#)